



Technical Data Sheet

Terostat-450



Alcoholic solution designed
for cleaning and to improve adhesion

Base: 2-Propanol

Issue: 25.11.2005

Product Description

Terostat-450 is an alcoholic solution designed for the cleaning of non sucking surfaces. It contains active ingredients that improve the adhesion of elastic adhesives and sealants on surfaces on which adhesion is usually difficult to achieve.

Application Areas

Terostat-450 is used for cleaning and if necessary to improve adhesion of elastic adhesives and sealants on metals, plastics and coated surfaces.

Technical Data

Colour:	colourless, clear
Density:	approx. 0.8 g/cm ³
Odour:	alcoholic
Consistency:	thin fluid
Flash off time:	10 - 60 min

Preliminary statement

Prior to application it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application

A thorough cleaning of the substrates is essential to achieve a serviceable adhesion on metals, plastics and coated surfaces.

Terostat-450 is applied finely and evenly by a suitable, clean cloth or paper. The cloth or paper should be changed by apparent contamination.

In order to control whether Terostat-450 covers the entire substrate, the product contains a UV indicator. It is particularly well visible under a UV lamp with a wave length of approx. 380 nm.

After withdrawal of the product the container should be closed tightly to prevent access of humidity. By exposure to water/humidity Terostat-450 loses its activity and becomes cloudy.

Cleaning

Splashes should be removed at once by an absorbing material.

Storage

Frost-sensitive	no
Recommended storage temperature	10°C to 25°C
Shelf-life	9 months in closed original packaging

Packaging

Aluminium bottle	1000 ml
Can	10 l

**Hazard Indications/
Safety Recommendations/
Transport Regulations**

see Safety Data Sheet

Important

The data above, particularly the recommendations for application and use of our products is based on our knowledge and experience. Due to different materials and conditions of application which are beyond our knowledge and control we strongly recommend carrying out sufficient tests in order to ensure that our products are suitable for the intended process and applications. Except for willful acts any liability based on such recommendations or any oral advice is hereby expressly excluded.

This Technical Data Sheet supersedes all previous editions.

Henkel KGaA
Location Heidelberg
D-69112 Heidelberg Germany
Phone: +49-6221-704-0
Fax: +49-6221-705-242
industrial-adhesives@henkel.com
www.industrial-adhesives.com